

**Product: R120 COS SPU**

Description This 120 COS red urethane belt features the toughest urethane coating on a spun polyester carcass. The thick urethane cover will resist cutting and abrasion from metal, glass, aluminum and other abrasive materials. Typically used for metal stamping, recycling, die cutting and brick manufacturing.

**Physical Properties**

Type: General Purpose Belt  
Color: Red  
# of Fabric Plies: 1 inter - woven  
Fabric Top Material: Urethane  
Fabric Bottom Material: Polyester (PET) fabric  
Profile Top side: Smooth Finish  
Profile Bottom side: Impregnated fabric  
Total Thickness: 0.187"

**Technical Data**

Temperature Range: -18 to 80 C  
Joining Methods: Finger Spliced, #4-2 Clipper, #25 Alligator, #187 Staple  
Antistatic: No  
Oil and Grease Resistant: Yes

**Pulley**

Min Pulley Diameter: 4" Spliced, 4" Clipper, 4" Alligator, 4" Staple  
Carrying Rollers: Yes  
Slider Bed: Yes  
Trough Installation: No

**Standards**

FDA food contact: Yes

Disclaimer:

The information contained in these Technical Data sheets is subject to change due to continuous developments where Data sheets are regenerated. Please check for the most up to date Data Sheets. If any other information is required please contact our sales team.