N NuTech C Conveyor C Components

Technical Data Sheet

1-495 McGeachie Drive Milton, ON, L9T 3L5 Toll Free: 1 (877) 639-2358 Phone: (905) 876-9339

Fax: (905) 876-9313

Product: Eagle Green 89 Non-Reinforced Textured Round

Description Eagle Green 89 Non-Reinforced Textured Round Belting (89 Shore A durometer)

that provides excellent abrasion resistance. A key feature of this belt is its

textured surface, which lowers its surface coefficient of friction.

Specifications

Profile shape: Round

Profile size: 10mm, 12mm, 15mm, 2mm, 3mm, 4mm, 5mm, 6mm, 7mm, 8mm

Reinforcement: None Color: Green

Compliancy: REACH, RoHS

Durometer: 89A

Material: Polyurethane Special Feature: Textured Package Length: 1001/30.5m

Physical Properties

Eagle Green 89 T Non-Reinforced Round Textured

Hardness	89A
FDA Compliant Materials	No
Coefficient of Friction	Stainless Steel: .50; Steel: .40; UHMW: .30
Temperature Range	-22°F to +150°F; -30°C to +66°C



Cross Section	Dimensions Ø			Working Load @ Percent Tension									
		Min Pulley Ø		4%		6%		8%		10%		Wt/ft	Wt/mtr
		inch	mm	lbs	N	lbs	N	lbs	N	lbs	N	lbs	kg
2mm	2	0.75	19	0.2	0.9	0.4	1.8	0.5	2.2	0.7	3.1	0.003	0.004
3mm	3	1	27	0.6	2.7	0.9	4	1.2	5,3	1,5	6.7	0.006	0.009
4mm	4	1.44	36	1	4.4	1.6	7.1	2.1	9.3	2.6	11.6	0.01	0.015
5mm	5	1.75	45	1.5	6.7	2.4	10.7	3.3	14.7	4.1	18.2	0.02	0.03
6mm	6	2.13	54	2.2	9.8	3.5	15.6	4.7	20.9	5.9	26.2	0.025	0.04
7mm	7	2.5	63	3	13,3	4.7	20.9	6.4	28.5	8	35,6	0.03	0.04
8mm	8	2.83	72	3.9	17.3	6.2	27.6	8.4	37.4	10.4	46.3	0.04	0.06
10mm	10	3.5	90	6,1	27,1	9.7	43.1	13.1	58.3	16.3	72.5	0.07	0.1
12mm	12	4.25	108	8.7	38.7	13.9	61.8	18.9	84.1	23.5	104.5	0.09	0.13
15mm	15	5.25	135	13.6	60.5	21.7	96.5	29.6	131.7	36.6	162.8	0.14	0.21
18mm	18	6.38	162	18.8	83,6	30.9	137.4	42.5	189	53	235.7	0.22	0.33
20mm	20	ं7	180	23.2	103.2	38.2	169.9	52.4	233.1	65.5	291.3	0.23	0.34

Dimensions are for reference only.