N NuTechC ConveyorC Components

## **Technical Data**

Sheet

1-495 McGeachie Drive Milton, ON, L9T 3L5 Toll Free: 1 (877) 639-2358 Phone: (905) 876-9339 Fax: (905) 876-9313

Product:	Eagle Green 89 Reinforced Textured Round
Description	Eagle Green 89 Reinforced Textured Round Belting constructed of polyurethane with an 89 Shore A durometer and reinforced with a polyester tensile cord that combines excellent abrasion resistance with high strength and low stretch. A key feature of this belt is its textured surface, which lowers its surface coefficient of friction.
Specifications	
Profile shape: Profile size: Reinforcement: Color: Compliancy: Durometer: Material:	Round 10mm, 12mm, 15mm, 18mm, 5mm, 6mm, 7mm, 8mm, 9mm Single Polyester Cord Green REACH, RoHS 89A Polyurethane
Special Feature: Package Length:	Textured 100'/30.5m

## **Physical Properties**

## Eagle Green 89 RT Reinforced Round Textured

Hardness	89A					
FDA Compliant Materials	No					
Coefficient of Friction	Stainless Steel: .50; Steel: .40; UHMW: .30					
Temperature Range	-22°F to +150°F; -30°C to +66°C					



	Warking Lozd @ Percent Tension												
Cross Section	Dimensions Ø mm	Min Pulley Ø		1%		2%		3%		4%		WVft	W/mb
		inch	mm	lbs	N	lbs	N	lbs	N	lbs	N	lbs	kg
5mm	5	2	50	1.7	7.4	5	22.2	10.2	45.5	15.8	70.1	0.02	0.03
6mm	6	2.38	60	2.4	10,6	7.2	32	14.7	65.5	22.7	101	0,025	0.04
7mm	7	2.75	70	3.3	14.5	9.8	43.5	20	89.1	30.9	137.4	0.03	0.05
8mm	8	3.13	80	4.3	18.9	12.8	56.8	26.2	116.4	40.4	179.5	0.04	0.06
10mm	10	3.94	100	6.6	29.6	20	88.8	40.9	181.9	63.1	280.5	0.06	0.09
12mm	12	4.75	120	9.6	42.6	28.8	127.9	58.9	262	90.8	403.9	0.09	0.13
15mm	15	5.9	150	15	66.5	44.9	199.8	92	409.3	141.9	631.1	0,14	0.21
18mm	18	7	180	21.5	95.8	64.7	287.8	132.5	589.4	204.3	908.8	0.22	0.33

Dimensions are for reference only.